

## Spicer Compact Plus

Spicer PN (Part Number)	Description	Series	Bearinc Cup (∅ mm)	Span (mm)	U-Joint (Type)	U-Joint (Grease)	Length (mm)	Slip (mm)	Max Angle	Flange Type	Holes	Holes (∅ mm)	Tube	Tube Dimension [mm]	Mounting holes [mm]	Mounting ho- les [distance mm]	CB Height [mm]	CB width	CB (∅ mm)	Shore	Remark
U-10076-00	U-Joint	COMPACT PLUS 2040	47,6	135,3	Service Free	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
U-10074-00	U-Joint	COMPACT PLUS 2040	47,6	135,3	Service Free	XD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
U-10075-00	U-Joint	COMPACT PLUS 2040	47,6	135,3	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
U-10085-00	U-Joint	COMPACT PLUS 2040	47,6	135,3	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	With cover on lubricator
U-10096-00	U-Joint	COMPACT PLUS 2040	47,6	135,3	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	1 Bearing Cup with lubricator
U-10101-00	U-Joint	COMPACT PLUS 2040	47,6	135,3	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	2 Bearing Cups with lubricator
U-10106-00	U-Joint	COMPACT PLUS 2040	47,6	135,3	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	4 Bearing Cups with lubricator
U-10087-00	U-Joint	COMPACT PLUS 2045/47	52	147,3	Service Free	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
U-10088-00	U-Joint	COMPACT PLUS 2045/47	52	147,3	Service Free	XD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
U-10080-00	U-Joint	COMPACT PLUS 2045/47	52	147,3	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
U-10086-00	U-Joint	COMPACT PLUS 2045/47	52	147,3	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	With cover on lubricator
U-10097-00	U-Joint	COMPACT PLUS 2045/47	52	147,3	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	1 Bearing Cup with lubricator
U-10102-00	U-Joint	COMPACT PLUS 2045/47	52	147,3	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	2 Bearing Cups with lubricator
U-10107-00	U-Joint	COMPACT PLUS 2045/47	52	147,3	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	4 Bearing Cups with lubricator
U-10078-00	U-Joint	COMPACT PLUS 2055	57	152,4	Service Free	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
U-10081-00	U-Joint	COMPACT PLUS 2055	57	152,4	Service Free	XD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
U-10084-00	U-Joint	COMPACT PLUS 2055	57	152,4	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
U-10089-00	U-Joint	COMPACT PLUS 2055	57	152,4	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	With cover on lubricator
U-10098-00	U-Joint	COMPACT PLUS 2055	57	152,4	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	1 Bearing Cup with lubricator
U-10103-00	U-Joint	COMPACT PLUS 2055	57	152,4	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	2 Bearing Cups with lubricator
U-10108-00	U-Joint	COMPACT PLUS 2055	57	152,4	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	4 Bearing Cups with lubricator
U-10090-00	U-Joint	COMPACT PLUS 2060	59	167,8	Service Free	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Spicer PN (Part Number)	Description	Series	Bearing Cup (∅ mm)	Span (mm)	U-Joint (Type)	U-Joint (Grease)	Length (mm)	Slip (mm)	Max Angle	Flange Type	Holes	Holes (∅ mm)	Tube	Tube Dimension (mm)	Mounting holes (mm)	Mounting ho- les [distance mm]	CB Height (mm)	CB width	CB (∅ mm)	Shore	Remark	
U-10091-00	U-Joint	COMPACT PLUS 2060	59	167,8	Service Free	XD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
U-10083-00	U-Joint	COMPACT PLUS 2060	59	167,8	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
U-10092-00	U-Joint	COMPACT PLUS 2060	59	167,8	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	With cover on lubricator	
U-10099-00	U-Joint	COMPACT PLUS 2060	59	167,8	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	1 Bearing Cup with lubricator	
U-10104-00	U-Joint	COMPACT PLUS 2060	59	167,8	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	2 Bearing Cups with lubricator	
U-10109-00	U-Joint	COMPACT PLUS 2060	59	167,8	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	4 Bearing Cups with lubricator	
U-10093-00	U-Joint	COMPACT PLUS 2065	65	172	Service Free	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
U-10095-00	U-Joint	COMPACT PLUS 2065	65	172	Service Free	XD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
U-10082-00	U-Joint	COMPACT PLUS 2065	65	172	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
U-10094-00	U-Joint	COMPACT PLUS 2065	65	172	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	With cover on lubricator	
U-10100-00	U-Joint	COMPACT PLUS 2065	65	172	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	1 Bearing Cup with lubricator	
U-10105-00	U-Joint	COMPACT PLUS 2065	65	172	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	2 Bearing Cups with lubricator	
U-10110-00	U-Joint	COMPACT PLUS 2065	65	172	Lube	STD	--	--	--	--	--	--	--	--	--	--	--	--	--	--	4 Bearing Cups with lubricator	
S-10043-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	419	180	27°	XS 155	4	13	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--	--
S-10025-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	327	110	27°	XS 180	4	15	T-10084-00	119,4 x 2,7	--	--	--	--	--	--	--	Slip joint with LT grease
S-10038-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	439	180	44°	XS 155	4	13	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--	--
S-10026-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	332	110	27°	XS 155	4	13	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--	--
S-10027-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	332	110	27°	XS 180	4	15	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--	--
S-10044-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	XD	327	110	27°	XS 155	4	13	T-10084-00	119,4 x 2,7	--	--	--	--	--	--	--	--
S-10030-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	327	110	27°	XS 180	4	15	T-10084-00	119,4 x 2,7	--	--	--	--	--	--	--	--
S-10023-00	Slip Joint SAE	COMPACT PLUS 2040	47,6	135,3	SF	STD	315,5	110	25°	SAE 1700	12	9,7	T-10084-00	119,4 x 2,7	--	--	--	--	--	--	--	--
S-10039-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	439	180	44°	XS 180	4	15	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--	--
S-10040-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	439	180	44°	XS 180	4	15	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--	Slip joint with LT grease

Spicer PN (Part Number)	Description	Series	Bearinc Cup (∅ mm)	Span (mm)	U-Joint (Type)	U-Joint (Grease)	Length (mm)	Slip (mm)	Max Angle	Flange Type	Holes	Holes (∅ mm)	Tube	Tube Dimension (mm)	Mounting holes (mm)	Mounting ho- les [distance mm]	CB Height [mm]	CB width	CB (∅ mm)	Shore	Remark
S-10045-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	XD	332	110	27°	XS 155	4	13	T-10083-00	99.2 x 4.1	--	--	--	--	--	--	--
S-10041-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	RE	STD	439	180	44°	XS 180	4	15	T-10083-00	99.2 x 4.1	--	--	--	--	--	--	With grease on cover tube
S-10031-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	419	180	27°	XS 180	4	15	T-10083-00	99.2 x 4.1	--	--	--	--	--	--	--
S-10046-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	RE	STD	332	110	27°	XS 180	4	15	T-10083-00	99.2 x 4.1	--	--	--	--	--	--	--
S-10047-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	RE	STD	327	110	27°	XS 155	4	13	T-10084-00	119.4 x 2.7	--	--	--	--	--	--	--
S-10048-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	327	110	27°	XS 180	4	15	T-10084-00	119.4 x 2.7	--	--	--	--	--	--	With greaser with cover on cover tube, slip joint with LT grease
S-10020-00	Slip Joint DIN	COMPACT PLUS 2040	47,6	135,3	SF	STD	347	110	44°	DIN 150	8	12,1	T-10084-00	119.4 x 2.7	--	--	--	--	--	--	--
S-10032-00	Slip Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	327	110	27°	XS 155	4	13	T-10084-00	119.4 x 2.7	--	--	--	--	--	--	--
S-10028-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	XD	360	110	27°	XS 155	4	13	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
S-10033-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	STD	347	110	27°	XS 180	4	15	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
S-10049-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	STD	461	180	44°	XS 180	4	15	T-10086-00	108.2 x 4.1	--	--	--	--	--	--	--
S-10034-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	STD	360	110	41°	XS 155	4	13	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
S-10050-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	STD	453	180	41°	XS 155	4	13	T-10086-00	108.2 x 4.1	--	--	--	--	--	--	--
S-10029-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	XD	347	110	27°	XS 180	4	15	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
S-10042-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	XD	453	180	41°	XS 155	4	13	T-10086-00	108.2 x 4.1	--	--	--	--	--	--	--
S-10051-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	RE	STD	347	110	27°	XS 180	4	15	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
S-10052-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	RE	STD	360	110	41°	XS 155	4	13	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
S-10021-00	Slip Joint DIN	COMPACT PLUS 2045/47	52	147,3	RE	STD	355	110	27°	DIN 180	8	14,1	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
S-10053-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	RE	STD	347	110	27°	XS 180	4	15	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	With grease on cover tube

Spicer PN (Part Number)	Description	Series	Bearinc Cup (∅ mm)	Span (mm)	U-Joint (Type)	U-Joint (Grease)	Length (mm)	Slip (mm)	Max Angle	Flange Type	Holes	Holes (∅ mm)	Tube	Tube Dimension (mm)	Mounting holes (mm)	Mounting ho- les [distance mm]	CB Height (mm)	CB width	CB (∅ mm)	Shore	Remark
S-10022-00	Slip Joint DIN	COMPACT PLUS 2045/47	52	147,3	SF	STD	355	110	27°	DIN 180	8	14,1	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
S-10054-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	STD	347	110	27°	XS 180	4	15	T-10090-00	118.2 x 4.1	--	--	--	--	--	--	--
S-10055-00	Slip Joint XS	COMPACT PLUS 2045/47	52	147,3	RE	STD	347	110	27°	XS 180	4	15	T-10090-00	118.2 x 4.1	--	--	--	--	--	--	--
S-10056-00	Slip Joint XS	COMPACT PLUS 2055	57	152,4	RE	STD	371	110	27°	XS 180	4	15	T-10087-00	118.4 x 5.2	--	--	--	--	--	--	--
S-10035-00	Slip Joint XS	COMPACT PLUS 2055	57	152,4	SF	STD	441	180	27°	XS 180	4	15	T-10087-00	118.4 x 5.2	--	--	--	--	--	--	Slip joint with LT grease
S-10057-00	Slip Joint XS	COMPACT PLUS 2055	57	152,4	SF	STD	441	180	27°	XS 180	4	15	T-10087-00	118.4 x 5.2	--	--	--	--	--	--	--
S-10036-00	Slip Joint XS	COMPACT PLUS 2055	57	152,4	SF	STD	371	110	27°	XS 180	4	15	T-10087-00	118.4 x 5.2	--	--	--	--	--	--	--
S-10037-00	Slip Joint XS	COMPACT PLUS 2060	59	167,8	SF	STD	378	110	30°	XS 180	4	15	T-10088-00	128.4 x 5.2	--	--	--	--	--	--	--
S-10058-00	Slip Joint XS	COMPACT PLUS 2060	59	167,8	RE	STD	378	110	30°	XS 180	4	15	T-10088-00	128.4 x 5.2	--	--	--	--	--	--	--
S-10059-00	Slip Joint XS	COMPACT PLUS 2060	59	167,8	SF	STD	448	180	30°	XS 180	4	15	T-10088-00	128.4 x 5.2	--	--	--	--	--	--	--
S-10060-00	Slip Joint XS	COMPACT PLUS 2065	65	172	SF	STD	406	110	27°	XS 180	4	15	T-10089-00	140.2 x 5.1	--	--	--	--	--	--	--
S-10061-00	Slip Joint XS	COMPACT PLUS 2065	65	172	RE	STD	406	110	27°	XS 180	4	15	T-10089-00	140.2 x 5.1	--	--	--	--	--	--	--
P-10016-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	163	--	27°	XS 155	4	13	T-10084-00	119.4 x 2.7	--	--	--	--	--	--	--
P-10017-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	163	--	27°	XS 180	4	15	T-10084-00	119.4 x 2.7	--	--	--	--	--	--	--
P-10018-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	163	--	27°	XS 180	4	15	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
P-10006-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	163	--	27°	XS 155	4	13	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
P-10027-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	196	--	44°	XS 155	4	13	T-10083-00	99.2 x 4.1	--	--	--	--	--	--	--
P-10019-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	176	--	27°	XS 155	4	13	T-10083-00	99.2 x 4.1	--	--	--	--	--	--	--
P-10028-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	XD	163	--	27°	XS 155	4	13	T-10084-00	119.4 x 2.7	--	--	--	--	--	--	--

Spicer PN (Part Number)	Description	Series	Bearing Cup (Ø mm)	Span (mm)	U-Joint (Type)	U-Joint (Grease)	Length (mm)	Slip (mm)	Max Angle	Flange Type	Holes	Holes (Ø mm)	Tube	Tube Dimension (mm)	Mounting holes (mm)	Mounting ho- les [distance mm]	CB Height (mm)	CB width	CB (Ø mm)	Shore	Remark
P-10005-00	Fixed Joint SAE	COMPACT PLUS 2040	47,6	135,3	SF	STD	151,5	--	27°	SAE 1700	12	9,7	T-10084-00	119,4 x 2,7	--	--	--	--	--	--	--
P-10029-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	RE	STD	196	--	44°	XS 180	4	15	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--
P-10030-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	XD	176	--	27°	XS 155	4	13	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--
P-10007-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	RE	STD	163	--	27°	XS 155	4	13	T-10084-00	119,4 x 2,7	--	--	--	--	--	--	--
P-10031-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	RE	STD	196	--	44°	XS 180	4	15	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--
P-10020-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	STD	176	--	27°	XS 180	4	15	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--
P-10008-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	RE	STD	176	--	27°	XS 180	4	15	T-10083-00	99,2 x 4,1	--	--	--	--	--	--	--
P-10032-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	SF	XD	163	--	27°	XS 180	4	15	T-10084-00	119,4 x 2,7	--	--	--	--	--	--	--
P-10033-00	Fixed Joint XS	COMPACT PLUS 2040	47,6	135,3	RE	STD	163	--	27°	XS 155	4	13	T-10084-00	119,4 x 2,7	--	--	--	--	--	--	U-Joint with greaser with covers on u-joint
P-10001-00	Fixed Joint DIN	COMPACT PLUS 2040	47,6	135,3	SF	STD	183	--	44°	DIN 150	8	12,1	T-10084-00	119,4 x 2,7	--	--	--	--	--	--	--
P-10002-00	Fixed Joint DIN	COMPACT PLUS 2040	47,6	135,3	SF	STD	183	--	44°	DIN 180	10	16,1	T-10084-00	119,4 x 2,7	--	--	--	--	--	--	--
P-10034-00	Fixed Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	STD	201	--	41°	XS 155	4	13	T-10086-00	108,2 x 4,1	--	--	--	--	--	--	--
P-10035-00	Fixed Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	XD	188	--	27°	XS 155	4	13	T-10085-00	118,8 x 3,4	--	--	--	--	--	--	--
P-10021-00	Fixed Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	STD	188	--	27°	XS 155	4	13	T-10085-00	118,8 x 3,4	--	--	--	--	--	--	--
P-10036-00	Fixed Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	XD	175	--	27°	XS 180	4	15	T-10085-00	118,8 x 3,4	--	--	--	--	--	--	--
P-10037-00	Fixed Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	XD	201	--	41°	XS 155	4	13	T-10086-00	108,2 x 4,1	--	--	--	--	--	--	--
P-10009-00	Fixed Joint XS	COMPACT PLUS 2045/47	52	147,3	RE	STD	175	--	27°	XS 180	4	15	T-10085-00	118,8 x 3,4	--	--	--	--	--	--	--
P-10003-00	Fixed Joint DIN	COMPACT PLUS 2045/47	52	147,3	RE	STD	183	--	27°	DIN 180	8	14,1	T-10085-00	118,8 x 3,4	--	--	--	--	--	--	--

Spicer PN (Part Number)	Description	Series	Bearinc Cup (∅ mm)	Span (mm)	U-Joint (Type)	U-Joint (Grease)	Length (mm)	Slip (mm)	Max Angle	Flange Type	Holes	Holes (∅ mm)	Tube	Tube Dimension (mm)	Mounting holes (mm)	Mounting ho- les [distance mm]	CB Height [mm]	CB width	CB (∅ mm)	Shore	Remark
P-10004-00	Fixed Joint DIN	COMPACT PLUS 2045/47	52	147,3	SF	STD	183	--	27°	DIN 180	10	16,1	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
P-10022-00	Fixed Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	STD	175	--	27°	XS 180	4	15	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	--
P-10010-00	Fixed Joint XS	COMPACT PLUS 2045/47	52	147,3	SF	STD	175	--	27°	XS 180	4	15	T-10090-00	118.2 x 4.1	--	--	--	--	--	--	--
S-10100-00	Slip Joint XS	COMPACT PLUS 2055	57	152,4	SF	XD	371	110	27°	XS 180	4	15	T-10087-00	118.4 x 5.2	--	--	--	--	--	--	--
P-10023-00	Fixed Joint XS	COMPACT PLUS 2055	57	152,4	SF	XD	188	--	27°	XS 180	4	15	T-10087-00	118.4 x 5.2	--	--	--	--	--	--	--
P-10011-00	Fixed Joint XS	COMPACT PLUS 2055	57	152,4	RE	STD	188	--	27°	XS 180	4	15	T-10087-00	118.4 x 5.2	--	--	--	--	--	--	--
P-10024-00	Fixed Joint XS	COMPACT PLUS 2055	57	152,4	SF	STD	188	--	27°	XS 180	4	15	T-10087-00	118.4 x 5.2	--	--	--	--	--	--	--
S-10101-00	Slip Joint XS	COMPACT PLUS 2060	59	167,8	SF	XD	378	110	30°	XS 180	4	15	T-10088-00	128.4 x 5.2	--	--	--	--	--	--	--
P-10025-00	Fixed Joint XS	COMPACT PLUS 2060	59	167,8	SF	STD	203	--	30°	XS 180	4	15	T-10088-00	128.4 x 5.2	--	--	--	--	--	--	--
P-10026-00	Fixed Joint XS	COMPACT PLUS 2060	59	167,8	SF	XD	203	--	30°	XS 180	4	15	T-10088-00	128.4 x 5.2	--	--	--	--	--	--	--
P-10012-00	Fixed Joint XS	COMPACT PLUS 2060	59	167,8	RE	STD	203	--	30°	XS 180	4	15	T-10088-00	128.4 x 5.2	--	--	--	--	--	--	--
S-10102-00	Slip Joint XS	COMPACT PLUS 2065	65	172	SF	XD	406	110	27°	XS 180	4	15	T-10089-00	140.2 x 5.1	--	--	--	--	--	--	--
P-10013-00	Fixed Joint XS	COMPACT PLUS 2065	65	172	SF	STD	211	--	27°	XS 180	4	15	T-10089-00	140.2 x 5.1	--	--	--	--	--	--	--
P-10014-00	Fixed Joint XS	COMPACT PLUS 2065	65	172	SF	XD	211	--	27°	XS 180	4	15	T-10089-00	140.2 x 5.1	--	--	--	--	--	--	--
P-10015-00	Fixed Joint XS	COMPACT PLUS 2065	65	172	RE	STD	211	--	27°	XS 180	4	15	T-10089-00	140.2 x 5.1	--	--	--	--	--	--	--
M-10019-00	Midship Assembly XS	COMPACT PLUS 2040	--	--	--	--	136	--	--	XS 155	4	13	T-10084-00	119.4 x 2.7	15 x 15	220 90	--	--	--	--	Fitted with center bearing B-10022-00
M-10020-00	Midship Assembly XS	COMPACT PLUS 2045/47	--	--	--	--	136	--	--	XS 155	4	13	T-10085-00	118.8 x 3.4	15 x 15	220 90	--	--	--	--	Fitted with center bearing B-10022-00
M-10021-00	Midship Assembly XS	COMPACT PLUS 2040	--	--	--	--	136	--	--	XS 180	4	15	T-10084-00	119.4 x 2.7	15 x 15	220 90	--	--	--	--	Fitted with center bearing B-10022-00

Spicer PN (Part Number)	Description	Series	Bearinc Cup (∅ mm)	Span (mm)	U-Joint (Type)	U-Joint (Grease)	Length (mm)	Slip (mm)	Max Angle	Flange Type	Holes	Holes (∅ mm)	Tube	Tube Dimension (mm)	Mounting holes (mm)	Mounting ho- les [distance mm]	CB Height (mm)	CB width	CB (∅ mm)	Shore	Remark
M-10022-00	Midship Assembly XS	COMPACT PLUS 2045/47	--	--	--	--	136	--	--	XS 180	4	15	T-10085-00	118.8 x 3.4	15 x 15	220	90	--	--	--	Fitted with center bearing B-10022-00
M-10023-00	Midship Assembly XS	COMPACT PLUS 2055	--	--	--	--	162	--	--	XS 180	4	15	T-10087-00	118.4 x 5.2	15 x 15	220	90	--	--	--	Fitted with center bearing B-10015-00
M-10024-00	Midship Assembly XS	COMPACT PLUS 2060	--	--	--	--	162	--	--	XS 180	4	15	T-10088-00	128.4 x 5.2	15 x 15	220	90	--	--	--	Fitted with center bearing B-10015-00
M-10025-00	Midship Assembly XS	COMPACT PLUS 2065	--	--	--	--	162	--	--	XS 180	4	15	T-10089-00	140.2 x 5.1	15 x 15	220	90	--	--	--	Fitted with center bearing B-10015-00
M-10026-00	Midship Assembly XS	COMPACT PLUS 2065	--	--	--	--	143,5	--	--	XS 180	4	15	T-10089-00	140.2 x 5.1	22	203	79,4	--	--	--	Fitted with center bearing 1000008707013
T-10083-00	Tube	COMPACT PLUS 2040	--	--	--	--	--	--	--	--	--	--	--	99.2 x 4.1	--	--	--	--	--	--	--
T-10084-00	Tube	COMPACT PLUS 2040	--	--	--	--	--	--	--	--	--	--	--	119.4 x 2.7	--	--	--	--	--	--	--
T-10085-00	Tube	COMPACT PLUS 2045/47	--	--	--	--	--	--	--	--	--	--	--	118.8 x 3.4	--	--	--	--	--	--	--
T-10086-00	Tube	COMPACT PLUS 2045/47	--	--	--	--	--	--	--	--	--	--	--	108.2 x 4.1	--	--	--	--	--	--	--
T-10087-00	Tube	COMPACT PLUS 2055	--	--	--	--	--	--	--	--	--	--	--	118.4 x 5.2	--	--	--	--	--	--	--
T-10088-00	Tube	COMPACT PLUS 2060	--	--	--	--	--	--	--	--	--	--	--	128.4 x 5.2	--	--	--	--	--	--	--
T-10089-00	Tube	COMPACT PLUS 2065	--	--	--	--	--	--	--	--	--	--	--	140.2 x 5.1	--	--	--	--	--	--	--
T-10090-00	Tube	COMPACT PLUS 2045/47	--	--	--	--	--	--	--	--	--	--	--	118.2 x 4.1	--	--	--	--	--	--	--
B-10022-00	Center Bearing Assembly	COMPACT PLUS 2040, COMPACT PLUS 2045/47	--	--	--	--	--	--	--	--	--	--	--	--	15 x 15	220	90	22	55	84	--
B-10015-00	Center Bearing Assembly	COMPACT PLUS 2055, COMPACT PLUS 2060, COMPACT PLUS 2065	--	--	--	--	--	--	--	--	--	--	--	--	15 x 15	220	90	26	70	84	--
1000008707013	Center Bearing Assembly	--	--	--	--	--	--	--	--	--	--	--	--	--	22	203	79,4	48,5	70	--	--

Spicer PN (Part Number)	Description	Series	Bearinc Cup (∅ mm)	Span (mm)	U-Joint (Type)	U-Joint (Grease)	Length (mm)	Slip (mm)	Max Angle	Flange Type	Holes	Holes (∅ mm)	Tube	Tube Dimension [mm]	Mounting holes [mm]	Mounting ho- les [distance mm]	CB Height [mm]	CB width	CB (∅ mm)	Shore	Remark
X-10070-00	Center Bearing Kit	COMPACT PLUS 2040, COMPACT PLUS 2045/47	--	--	--	--	--	--	--	--	--	--	--	--	15 x 15	220	90	26	75	84	Including glue and needle
X-10071-00	Center Bearing Kit	COMPACT PLUS 2055	--	--	--	--	--	--	--	--	--	--	--	--	15 x 15	220	90	26	85	84	Including glue and needle
X-10072-00	Center Bearing Kit	COMPACT PLUS 2055, COMPACT PLUS 2060, COMPACT PLUS 2065	--	--	--	--	--	--	--	--	--	--	--	--	15 x 15	220	90	26	70	84	B-10015-00 and bolts
A-10001-00	Sleeve Muff As-sembly	COMPACT PLUS 2040	--	--	--	--	170	--	--	--	--	--	T-10084-00	119.4 x 2.7	15 x 15	220	90	--	--	--	Fitted with center bearing kit X-10070-00. Related MIS Yoke Shaft kit: X-10067-00. Use boot 1000008401011.
A-10002-00	Sleeve Muff As-sembly	COMPACT PLUS 2045/47	--	--	--	--	179	--	--	--	--	--	T-10085-00	118.8 x 3.4	15 x 15	220	90	--	--	--	Fitted with center bearing kit X-10070-00. Related MIS Yoke Shaft kit: X-10068-00. Use boot 1000008401011.
A-10003-00	Sleeve Muff As-sembly	COMPACT PLUS 2055	--	--	--	--	192	--	--	--	--	--	T-10087-00	118.4 x 5.2	15 x 15	220	90	--	--	--	Fitted with center bearing kit X-10071-00. Related MIS Yoke Shaft kit: X-10069-00. Use boot 1000008401015.
X-10067-00	MIS Yoke shaft kit	COMPACT PLUS 2040	47,6	135,3	SF	STD	--	110	27°	--	--	--	T-10084-00	119.4 x 2.7	--	--	--	--	--	--	To be used with Sleeve Muff Assembly A-10001-00. Use boot 1000008401011.
X-10068-00	MIS Yoke shaft kit	COMPACT PLUS 2045/47	52	147,3	SF	STD	--	110	27°	--	--	--	T-10085-00	118.8 x 3.4	--	--	--	--	--	--	To be used with Sleeve Muff Assembly A-10002-00. Use boot 1000008401011.
X-10069-00	MIS Yoke shaft kit	COMPACT PLUS 2055	57	152,4	SF	STD	--	110	27°	--	--	--	T-10087-00	118.4 x 5.2	--	--	--	--	--	--	To be used with Sleeve Muff Assembly A-10003-00. Use boot 1000008401015.